

GH Gas Hydraulic Range Heavy Duty Airless Sprayers for your Heavy Duty Jobs



PROFESSIONAL ADVANTAGES

- Convertible Gas Electric with no tools
- High efficient hydraulic pumping power
- Upgraded with ProConnect[™] & MaxLife[™] piston rod

MATERIALS

Latex - Acrylic - Emulsions - Block fillers - Intumescents - Light fillers - Plasters





Gas Hydraulic Range - Heavy Duty Airless **Sprayers for your Heavy Duty Jobs**



Flow-through Filter System

- Handtight Filter removes with the cap
- Debris stays inside the colour coded filters
- Flow-through for optimal use of the total filter surface

ABS Shroud

- Won't break, bend or rust under working conditions
- Easy to clean



ProConnect™ system CLOSED with pump in.



ProConnect system OPEN with pump in.



ProConnect system OPEN without pump in.



High Efficiency Hydraulic Motor

- Fast change-over design for uniform pressure at the gun
- 100% o'ring sealed fittings
- No hydraulic stalls through special ramp design



High Capacity Cooling System

- Cooling fins on reservoir deflect heat faster
- Extra large oil reservoir
- 'Turbo" fan for continuous cooling

Comfortable Cart Design

- Compact and easy to transport and handle around a job site
- Chromed and welded to last for years
- of hard use
- Telescoping handle for quick hose unwrapping



PRO• CONNECT View movie clip at:



www.pro-connect.eu

GH

SPECIFICATIONS

- with electric engine

		GH 200	GH 230	GH 300
Part Number		255095	253965	253968
Max. Tip Size	- with gas engine	0.047"	0.053"	0.057"
	- with electric engine	0.039"	0.039"	0.039"
Max. Flow		8.1 l/min. (2.15 gpm)	8.9 l/min. (2.35 gpm)	11.3 l/min. (3.0 gpm)
Max. Pressure		230 bar (3300 PSI)	230 bar (3300 PSI)	230 bar (3300 PSI)
Weight		73 kg (160 lbs)	76 kg (168 lbs)	88 kg (195 lbs)
Max. Hose length		60 m	75 m	90 m
Honda® GX engine output		4.1 kW	4.8 kW	6.6 kW
Honda® engine displacement		163 cm ³	196 cm ³	270 cm ³
Fuel tank capacity		3.61	3.61	6.01
Fuel consumption		313 g/kW.hr	313 g/kW.hr	313 g/kW.hr
Includes				
Gun		TexSpray™ Blue	Silver Plus	Silver Plus
Tip & guard		RACX531 and RACX427	LTX517	LTX517
BlueMax™ II hose		3/8" x 15m	3/8" x 15m	3/8" x 15m
Whip + fittings		1/4" x 0.90m	1/4" x 0.90m	1/4" x 0.90m



GRACO N.V. • Fluid Handling Solutions

www.graco.be (Europe)

Tel. (32) 89 770 700 • Fax (32) 89 770 777

Convertible system: never miss a job or suffer downtime again because of power issues.

© 2007 Graco N.V. · Form No. 320585 E (rev.D)· 10/07 · Printed in Europe Graco is certified ISO 9001.

ACCESSORIES

Guns

243283 Silver Plus gun, 2-finger trigger, RAC X (517) +

246240 Silver Plus gun, 2-finger

trigger, RAC 5 (517) + guard

246468 Silver Flex gun, 2-finger trigger, RAC X (517) +

guard

241705 TexSpray blue gun, 4-finger trigger,

GHD (531) + guard

EasyOut™ pump filters

244071 30 mesh, grey 60 mesh, black 244067 244068 100 mesh, blue

244069 200 mesh, red

BlueMax™ Hose (230 bar)

240794 1/4" x 15 m 1/4" x 20 m 241272 223771 1/4" x 30 m 240797 3/8" x 15 m 241275 3/8" x 30 m

Specifics

248946 Electric motor kit 3.0 HP, 220V

288472 GH 200/230/300

crush-proof strainer

287541 Convertible 110 to 200

liter suction kit. Fits all GMax[™] II and GH sprayers.

Tips

286XXX RAC®5 tips

RAC X™ long life tips RAC X™ WideRac tip LTXXXX WRXXXX

Guards

RAC®5 guard 243161 246215 RAC®X guard

Liquids

206994 TSL™ 0.25I 243103 Pump Armor™ 11 245133 Pump Armor 3.8 I 207428 Hydraulic oil, 11



Crush-proof Rock Catcher Inlet Screen

- Longer size: larger filtering surface
- Internal design: resistant to real life job conditions
- Dented outlet piece: material suction down to the bottom of the bucket

MaxLife™ Technology

Exclusive coating technology used on the piston rod and sleeve drastically improves life.

