

ACCESSORIES

- Gun**
245820 Spack gun bare
(no guard and no tip)
350 bar
224991 Mastic Flo-gun
without diffuser
(275bar) W/GHD 535,
Guard, 1/2" and 3/8"
adapter

- Adapters**
207947 1/2" gun swivel
159239 Adapter 1/2" x 3/8"

- Hoses**
277331 1/2" x 15m. Fluid hose
191239 Whip 3/8" x 3,3m.
240797 BlueMax™ II hose
3/8" x 15m (FBE)

- Filter housing kit**
287995 Accessory kit with
1/2" porting

- Pump lower**
287946 Mark X™ pump lower
with ProConnect™

- Hopper**
241318 90 liter hopper kit
248531 Bag roller kit
243428 Wheel kit

- Suction kit**
243167 Container suction kit

- Air spray kit**
244052 Air atomizer kit with
air hose

- Tips**
TMXxxx Texture reversible tips

TMX531	TMX541	TMX651	TMX671
TMX535	TMX545	TMX661	

- Guard**
243161 RAC® 5 HandTite™

- Liquids**
206994 TSL™ 0.25l
243103 Pump Armor™ 1l
245133 Pump Armor 3.8 l



MARK X™ ProConnect™
Twice the Mark V™ for airless plastering applications



PROFESSIONAL ADVANTAGES

- Double your production - More than twice the output of a Mark V
- Double your reach
- Double your turnover

MATERIALS

Plasters - Intumescent - Insulation - Roofing - Paints


Texture Applications
MARK X™ ProConnect





MARK X™ ProConnect™

Twice the Mark V™ for airless plastering applications



1
Unscrew paint line



2
Open latch that opens front cover



3
Remove pin.
Pump lower is free.



EXCLUSIVE PUMP ATTACHMENT
Remove and replace your entire pump lower:
On the job - without any tools - in seconds

MARK X™ ProConnect™ SPECIFICATIONS

Part Numbers:

220V - European version

220V - Italian, Swiss

Max. tip size

Flow - L/Min (Gpm)

Max. pressure - bar (PSI)

Weight - kgs (lbs)

SmartControl™ version

Motor type

Motor rating - kW (HP)

Mark X™ ProConnect

249627

249628

with paint: 0.045"

with plaster: 0.051" +

with paint: 7.6 (2.0)

with plaster: 9.1 (2.4)

230 (3300)

63 (139)

2.0

DC "brushless"

3.0 (4.0)

The Mark X™ ProConnect™ ships complete and ready to spray! Accessory box standard: 245820 Spack gun, TMX535 Texture tip for fine finish plaster work, TMX545 Texture tip for fast application, 243161 Rac 5 HandTite™ guard, 207947 1/2" gun swivel, 159239 x 2 Fitting 1/2" x 3/8", 191239 Whip 3/8" x 3.3 meter, 277331 1/2" x 15m. Fluid hose, 222297 45° adapter (when using hopper), 197193 Tool, 111733 Adjustable wrench, 206994 0,25 lit TSL™



Field tested with 30 meters vertical + 18 meters horizontal = 48 meters of hose



Amp switch
10A to 14A
Work on any job site even when the available power is low



Optimized fluid passages

1/2" porting
Smooth fluid passages

1/2" hose coupled with a 3,3 meter whip hose for flexibility



HD Endurance™ pump

Chromex rod

Outlasts standard chromed pistons

Lowered inlet check

Brings the suction power down where it is needed

Ceramic balls

Higher resistance against wear with abrasive materials

Spring loaded

Fast priming and fast closing of the inlet ball for improved performance

Extra large fluid passages

To handle thicker products

Big pneumatic wheels

Rolls easily over rough terrain and stairs
Inner tube facilitates repair



Spack gun

Lightweight

Reducing operator fatigue

1/2 SST fluid passages with 45° bend

Optimized for thicker fluids

Enlarged needle and seats

Longer life and allows for smooth spraying with heavy materials

Formed grip handle

Comfort in spraying
Non slip



DC Brushless Motor

Totally enclosed & fan cooled for longer life

Compact design for easy handling

Fast response time for high efficiency

SmartControl™ 2.0

Instant tip size learning:

- Sprayer immediately adjusts flow and pressure

Higher working pressure:

- Translates into a uniform spray pattern with no edges (less scraping)

Data center:

- pressure indicator, liter counter, etc



Power factor

Another Graco's exclusive.
Transforms the available electric power into pumping power!